



AS-5M

Amerisolar's photovoltaic modules are designed for large electrical power requirements. With a 30-year warranty, AS-5M offers high-powered, reliable performance for both on-grid and off-grid solar projects.

Key Features



- High module conversion efficiency up to 16.45% through advanced manufacturing technology.
- Low degradation and excellent performance under high temperature and low light conditions.
- Robust aluminum frame ensures the modules to withstand wind loads up to 2400Pa and snow loads up to 5400Pa.
- Positive power tolerance of 0 ~ +3 %.
- High ammonia and salt mist resistance.
- Potential induced degradation (PID) resistance.

Quality Certificates

- IEC61215, IEC61730, IEC62716, IEC61701, UL1703, ETL, CE, MCS, CEC, Israel Electric, Kemco
- ISO9001:2008: Quality management system
- ISO14001:2004: Environmental management system
- OHSAS18001:2007: Occupational health and safety management system

Special Warranties

- 12 year limited product warranty.
- Limited power warranty: 12 years 91.2% of the nominal power output, 30 years 80.6% of the nominal power output.



**Passionately
committed to
delivering innovative
energy solution**

Electrical Characteristics

Electrical parameters at STC						
Nominal Power (P_{max})	185W	190W	195W	200W	205W	210W
Open Circuit Voltage (V_{oc})	44.8V	45.0V	45.1V	45.2V	45.4V	45.6V
Short Circuit Current (I_{sc})	5.45A	5.54A	5.63A	5.72A	5.81A	5.90A
Voltage at Nominal Power (V_{mp})	36.3V	36.5V	36.7V	36.9V	37.1V	37.3V
Current at Nominal Power (I_{mp})	5.10A	5.21A	5.32A	5.43A	5.53A	5.64A
Module Efficiency (%)	14.49	14.88	15.27	15.67	16.06	16.45

STC: Irradiance 1000W/m², Cell temperature 25°C, AM1.5

Electrical parameters at NOCT						
Nominal Power (P_{max})	136W	140W	144W	147W	151W	155W
Open Circuit Voltage (V_{oc})	41.2V	41.4V	41.5V	41.6V	41.8V	42.0V
Short Circuit Current (I_{sc})	4.41A	4.49A	4.56A	4.63A	4.71A	4.78A
Voltage at Nominal Power (V_{mp})	33.0V	33.2V	33.4V	33.6V	33.8V	33.9V
Current at Nominal Power (I_{mp})	4.13A	4.22A	4.32A	4.38A	4.47A	4.58A

NOCT: Irradiance 800W/m², Ambient temperature 20°C, Wind speed 1 m/s

Mechanical Characteristics

Cell type	Monocrystalline 125x125mm(5x5inches)
Number of cells	72 (6x12)
Module dimension	1580x808x45mm(62.20x31.81x1.77inches)
Weight	15.5kg(34.2lbs)
Front cover	3.2mm(0.13inches) low-iron tempered glass
Frame	Anodized aluminum alloy
Junction box	IP65 or IP67
Cable	4mm ² (0.006inches ²), 900mm(35.43inches)
Connector	MC4 or MC4 compatible
Standard packaging	22pcs/pallet
Module quantity per container	264pcs/20'GP, 616pcs/40'GP

Temperature Characteristics


Nominal Operating Cell Temperature (NOCT)	45°C±2°C
Temperature Coefficients of P_{max}	-0.43%/°C
Temperature Coefficients of V_{oc}	-0.33%/°C
Temperature Coefficients of I_{sc}	0.056%/°C

Maximum Ratings


Operating Temperature	-40°C to +85°C
Maximum System Voltage	1000V DC
Maximum Series Fuse Rating	10A

Specifications in this datasheet are subject to change without prior notice.


Drawings



I-V Curves



Current-Voltage and Power-Voltage Curves at Different Irradiances



Current-Voltage Curves at Different Temperatures

Worldwide Energy and Manufacturing USA Co., Limited

Tel: +1-650-777-7606

Email: sales@weamerisolar.com

www.weamerisolar.com

EN-V1.0 Copyright © 2015 Worldwide Energy and Manufacturing USA Co., Limited.