



- Pure sine wave solar inverter
- Output power factor 1
- Selectable high power charging current
- Wide DC input range
- Selectable input voltage range for home appliances and personal computers
- Configurable AC/Solar input priority via LCD setting
- Compatible with mains voltage or generator power
- Auto restart while AC is recovering
- Overload and short circuit protection
- Smart battery charger design for optimized battery performance
- Cold start function
- Optional anti-dusk kit

2023/01/11 15:19:33

TrICCI All-in-One Off Grid Inverter

| MODEL | 12/1000 20-50P | 12/1000 20-40M | 24/2000 20-50P | 24/2000 25-40M | 24/3000 25-50P | 24/3000 25-40M | 24/3000 60-60M | 48/5000 60-50P | 48/5000 60-60M | |
|---------------------------------------|---|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|--|
| Rated Power | 1000VA/1000W | | 2000VA/2000W | | 3000VA / 3000W | | | 5000VA / 5000W | | |
| INPUT | | | | | | | | | | |
| Voltage | 230 VAC | | | | | | | | | |
| Selectable Voltage Range | 170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances) | | | | | | | | | |
| Frequency Range | 50 Hz/60 Hz (Auto sensing) | | | | | | | | | |
| OUTPUT | | | | | | | | | | |
| AC Voltage Regulation (Batt. Mode) | 230VAC ± 5% | | | | | | | | | |
| Surge Power | 2000VA | | 4000VA | | 6000VA | | | 10000VA | | |
| Efficiency (Peak) | 90% ~ 93% | | | | | | | | | |
| Transfer Time | 10 ms (For Personal Computers) ; 20 ms (For Home Appliances) | | | | | | | | | |
| Waveform | Pure sine wave | | | | | | | | | |
| BATTERY | | | | | | | | | | |
| Battery Voltage | 12 VDC | | 24 VDC | | | | | 48 VDC | | |
| Floating Charge Voltage | 13.5 VDC | | 27 VDC | | | | | 54 VDC | | |
| Overcharge Protection | 16 VDC | | 31 VDC | | 33 VDC | | | 63 VDC | | |
| SOLAR CHARGER & AC CHARGER | | | | | | | | | | |
| Solar Charger type | PWM | MPPT | PWM | MPPT | PWM | MPPT | | PWM | MPPT | |
| Maximum PV Array Open Circuit Voltage | 55 VDC | 102 VDC | 80 VDC | 102 VDC | 80 VDC | 102 VDC | 145 VDC | 105 VDC | 145 VDC | |
| Maximum PV Array Power | 600 W | 500 W | 1200 W | 1000 W | 1200 W | 1000 W | 1500 W | 2400 W | 3000 W | |
| MPP Range @ Operating Voltage | N/A | 17 ~ 80 VDC | N/A | 30 ~ 80 VDC | N/A | 30~80 VDC | 30~115 VDC | N/A | 60 ~ 115 VDC | |
| Maximum Solar Charge Current | 50 A | 40 A | 50 A | 40 A | 50 A | 40 A | 60 A | 50 A | 60 A | |
| Maximum AC Charge Current | 20 A | 20 A | 20 A | 25 A | 25A | 25A | 60 A | 60 A | 60 A | |
| Maximum Charge Current | 50 A | 60 A | 50 A | 60 A | 70 A | 60 A | 120 A | 110 A | 120 A | |
| PHYSICAL | | | | | | | | | | |
| Dimension, D x W x H (mm) | 88 x 225 x 320 | | | | 100 x 285 x 334 | | 100 x 300 x 440 | 100 x 300 x 440 | | |
| Net Weight (kgs) | 5.0 | 5.1 | 5.5 | 5.5 | 6.3 | 6.5 | 9.5 | 8.5 | 9.7 | |
| Communication Interface | USB/RS232 | | | | | | | | | |
| ENVIRONMENT | | | | | | | | | | |
| Humidity | 5% to 95% Relative Humidity (Non-condensing) | | | | | | | | | |
| Operating Temperature | -10°C to 50°C | | | | | | | | | |
| Storage Temperature | -15°C to 60°C | | | | | | | | | |

Product specifications are subject to change without further notice.